



NOTES: MATERIAL & FINISH
 1.INSULATOR:HIGH-TEMP THERMOPLASTIC, UL94V-0
 COLOR:NATURAL
 2.CONTACT:COPPER ALLOY
 PLATING:TIN OR GOLD FLASH OVERALL NICKEL
 UNDER PLATED
 3.ORDER INFORMATION: 3753K -XXXN- 07 X Δ

ENTERY INDUSTRIAL CO., LTD.
 APR 14 2014
 R&D D.C.C. ISSUED

PACKING: R: PLASTIC REEL
 E: TUBE
 L: PAPER REEL
 TYPE:
 N: STANDARD
 PIN NO.
 PLATING: E: TIN
 F: CONTACT GOLDFLASH,
 FITTING NAIL TIN
 ΔQ: CONTACT MATTE-TIN
 FITTING NAIL TIN

Δ3753K: 1.0 WIRE TO BOARD SMT R/A DUAL ROW
 (HALOGEN-FREE)

PIN NO.	A	B	C
06	2.0	5.6	4.2
08	3.0	6.6	5.2
10	4.0	7.6	6.2
12	5.0	8.6	7.2
14	6.0	9.6	8.2
16	7.0	10.6	9.2
18	8.0	11.6	10.2
20	9.0	12.6	11.2
22	10.0	13.6	12.2
24	11.0	14.6	13.2
26	12.0	15.6	14.2
28	13.0	16.6	15.2
30	14.0	17.6	16.2
32	15.0	18.6	17.2
34	16.0	19.6	18.2
36	17.0	20.6	19.2
38	18.0	21.6	20.2
40	19.0	22.6	21.2
42	20.0	23.6	22.2
44	21.0	24.6	23.2
46	22.0	25.6	24.2
48	23.0	26.6	25.2
50	24.0	27.6	26.2

3753-X10N-07X

3753-X20N-07X

3753-X30N-07X



SECTION A-A

CUSTOMER: 恩得利工業股份有限公司
 E&T ENTERY INDUSTRIAL CO., LTD.

REVISIONS	CHK	DATE
Δ RE201208014	Max	12/25/12
Δ RE201210002		
Δ RE201211010	JUNO	11/13/12
Δ RE200908032	JUNO	09/09/09
Δ RE081108	John	07/21/09
Δ RE200904035	John	05/07/09

GENERAL TOLERANCE UNLESS OTHERWISE SPECIFIED
 X.X ±0.25
 X.XX ±0.13
 X.XXX ±0.30'
 ANG. ±0.30'
 DRAWN: John AUG-17-2007
 CHECKED: [Signature]
 APPROVED: [Signature] 10/13
 SHEET: 1/1

PART NO. Δ 3753K-XXXN-07X
 TITLE: 1.0 WTB SMT R/A TYPE DUAL ROW
 UNIT: MM SCALE: 5:1 SIZE: A4 REV: F