



NOTES: MATERIAL & FINISH  
 △ 1.INSULATOR:HIGH-TEMP THERMOPLASTIC, UL94V-0  
 △ COLOR:NATURE OR BLACK  
 2.CONTACT:COPPER ALLOY  
 PLATING:GOLD FLASH OVERALL NICKEL UNDER PLATED  
 △△△ 3.ORDER INFORMATION: 3760K -XXXX - 71,J1 X



PACKING  
 R: PLASTIC REEL  
 E: TUBE  
 D: VACUUM AND HUMIDIYT LABEL  
 L: PAPER REEL  
 TYPE 71: NATURE  
 J1: BLACK △  
 C: CAP  
 Y: CAP&PRINTING DATA CODE  
 M: ADD MYLAR △

PIN  
 PLATING:  
 △ J: 10u" GOLD, FITTING NAIL TIN  
 F: GOLD FLASH  
 △△ H: CONTACT AREA 15u"(MIN) GOLD,  
 OTHER AREA GOLD FLASH  
 1.0 WTB SMT V/T TYPE DUAL ROW(HALOGEN FREE)

ENTERY INDUSTRIAL CO., LTD.  
 APR 15, 2014  
 R&D D.C.C. ISSUED

PIN NO.	A	B	C	D
10	4.0	7.7	5.65	5.7
12	5.0	8.7	6.65	6.7
16	7.0	10.7	8.65	8.7
18	8.0	11.7	9.65	9.7
20	9.0	12.7	10.65	10.7
24	11.0	14.7	12.65	12.7
30	14.0	17.7	15.65	15.7
34	16.0	19.7	17.65	17.7
40	19.0	22.7	20.65	20.7
50	24.0	27.7	25.65	25.7

△ MYLAR DRAWING

CUSTOMER		ENTERY INDUSTRIAL CO., LTD.	
GENERAL TOLERANCE UNLESS OTHERWISE SPECIFIED	DRAWN Max AUG-24-2010	PART NO. △△△ 3760K-XXXX-71,J1X	TITLE: 1.0 WTB SMT V/T TYPE DUAL ROW
X.X ±0.30	CHECKED		
X.XX ±0.20	APPROVED		
X.XXX ANG. ±0'30"			
SER REVISIONS	CHK DATE	SHEET 1/1	UNIT MM SCALE 5:1 SIZE A4 REV K

SER	REVISIONS	CHK	DATE
△	RE201308015	Ceres	04/15/14
△	RE201308015	Juno	09/04/13
△	RE201208014	MAX	12/26/12
△	RE201209003	JIMMY	10/16/12
△	REN120209	KAZ	02/15/12
△	RE201201006	JIMMY	01/12/12

RECOMMENDED PCB LAYOUT