

NOTE:  
 1.INSULATOR:HIGH-TEMPERATURE THERMOPLASTIC UL94V-0  
 COLOR:BLACK  
 2.CONTACT:COPPER ALLOY  
 PLATING:MATTE-TIN OR GOLD FLASH OVERALL NICKEL UNDER PLATED  
 3.FITTING NAIL:COPPER ALLOY  
 PLATING:MATTE-TIN(LEAD FREE) PLATED  
 ORDER INFORMATION: 3808K-X XX X - 03,23 X

PACKING: R: PLASTIC REEL  
 L: PAPER REEL  
 E: TUBE

TYPE  
 03: STANDARD  
 23: CARRIER DIFFERENT Δ


N: STANDARD  
 M: ADD MYLAR(2-4PIN)  
 PIN NO.

PLATING: F: GOLD FLASH  
 Q: MATTE-TIN(LEAD FREE)  
 Δ: CONTACT AREA 10u"(min) GOLD  
 OTHER AREA GOLD FLASH

1.25 WTB SMT R/A TYPE SINGLE ROW  
 SUNK INTO THE BOARD TYPE  
 (HALOGEN FREE)

ENTERY INDUSTRIAL CO., LTD.  
 DEC - 8. 2014  
 R&D D.C.C. ISSUED

PIN NO.	A	B	C	D
02	7.65	1.25	3.77	
03	8.90	2.50	5.02	
04	10.15	3.75	6.27	2.50
05	11.40	5.00	7.52	3.75
06	12.65	6.25	8.77	5.00
07	13.90	7.50	10.02	6.25
08	15.15	8.75	11.27	7.50
09	16.40	10.00	12.52	8.75
10	17.65	11.25	13.77	10.00
11	18.90	12.50	15.02	11.25
12	20.15	13.75	16.27	12.50
13	21.40	15.00	17.52	13.75
14	22.65	16.25	18.77	15.00
15	23.90	17.50	20.02	16.25



<b>CUSTOMER</b>		恩得利工業股份有限公司 E&T ENTERY INDUSTRIAL CO., LTD.	
DRAWN Joan JUL-01-2009		PART NO. 3808K-XXXX-03,23X	
CHECKED		TITLE: 1.25 WTB SMT R/A TYPE SINGLE ROW SUNK INTO THE BOARD TYPE	
APPROVED		SHEET 1/1	
UNIT MM	SCALE 5:1	SIZE A4	REV E

REVISIONS	CHK	DATE
RE201409012	Juno	11/26/14
RE201310020	Juno	10/25/13
REN110808	KAZ	08/04/11
REN90712	JOAN	07/13/09

GENERAL TOLERANCE  
 UNLESS  
 OTHERWISE SPECIFIED  
 X.X ±0.30  
 X.XX ±0.20  
 X.XXX ±0.10  
 ANG. ±0.30'