

TO

SPECIFICATION FOR APPROVAL

DESCRIPTION: Pitch 0.80mm Board To Board Connector, V/T, SMT Type Female Post

CUSTOMER PROD.NO/DWG.NO:

E&T PROD.NO: 1134K-XXXX-XXX

APPROVAL SHEET NO:

E&T DWG. NO./DOCUMENT: 1134K-XXXX-XXX

REV: A1

PLEASE RETURN TO US ONE COPY OF "SPECIFICATION FOR APPROVAL" WITH YOUR APPROVED SIGNATURES.



APPROVED SIGNATURES			



**ENTERY INDUSTRIAL CO., LTD.
E&T ELECTRONICS (DONG GUAN) CO., LTD.
E&T ELECTRONICS (SU ZHOU) CO., LTD.**

ENTERY INDUSTRIAL CO., LTD.

**Title :Pitch 0.80mm Board To Board Connector,
V/T, SMT Type Female Post**

Release History		Title: Pitch 0.80mm Board To Board Connector, V/T, SMT Type Female Post	
A1	11,18'2011	This Document Contains Information That Is Proprietary To E&T And Should Not Be Used Without Written Permission	
Rev	Description		
Document No.		Prepared By: Juno Chen	Date: 09,14'2009
1134K-XXXX-XXX		Checked By: 	Date: 12, 29, 2011
		Approved By: 	Date:

ENTERY INDUSTRIAL CO., LTD.

PRODUCT SPECIFICATION

1. SCOPE :

This specification covers the 0.8 mm pitch board To board SMT type connector series.

2. PRODUCT NAME AND PART NUMBER :

Product Name	E&T Part Number
0.80mm Board To Board Connector, V/T, SMT Type Female Post(Lead Free)	1134K-XXXX-XXX

3. RATINGS :

Item	Standard	
Rated Voltage (MAX.)	50 V	AC
Rated Current (MAX.)	0.5A	
Ambient Temperature Range	-40 ⁰ C ~ +80 ⁰ C	

*Including terminal temperature rise

4.PERFORMANCE :

4- 1 Electrical Performance

Item		Test Condition	Requirement
4-1-1	Contact Resistance	Test Current: 100 mA Max. Test Voltage: 20mV Max Test Method: MIL-STD-202F, Method 303	50 mΩ MAX.
4-1-2	Insulation Resistance	Test Voltage: 100VAC. Test Duration: 1 minutes. Test Method: MIL-STD-202, method 302	Initial: 500 MΩ Min Final: 100 MΩ Min.
4-1-3	Dielectric Strength	Test Voltage: 200V AC. Test Time: 60 sec. Test Method: MIL-STD-202, Method 301.	No Breakdown

ENTERY INDUSTRIAL CO., LTD.

4-2 Mechanical Performance

Item		Test Condition	Requirement	
4-2-1	Insertion Force And Withdrawal Force	Test Speed: 25±3 mm/min. Test Method: MIL-STD-1344A, Method 2016.	Insertion Force Max : 0.09kgf X total terminals	
			Withdrawal Force(Min): 0.01kgf X total terminals	
4-2-2	Terminal / Housing Retention Force	Test Speed: 25mm/min.	0.5kgf (Min)	
4-2-3	Durability	The contacts of connector shall be subject to 50 cycles of mating and unmating.	Contact Resistance	
			Initial Value	≤ 50 mΩ
			Final Value	≤ 70 mΩ


4-3 Environmental Performance and Others

Item		Test Condition	Requirement	
4-3-1	Vibration	Amplitude : 1.5 mm Frequency range: 10~55~10 Hz in 1 minute Duration: 2 hours in each X.Y.Z axes Current: 100mA. Test Method: MIL-STD-202F, Method 201	Appearance	No Damage
			Contact Resistance	≤ 70 mΩ
			Discontinuity	1μsec
4-3-2	Heat Resistance	Temperature: 80±2°C Duration: 96 hours Test Method: MIL-STD-202, Method 108.	Appearance	No Damage
			Contact Resistance	≤ 70 mΩ
4-3-3	Cold Resistance	Temperature: -40±2°C Duration: 96 hours Test Method: JIS C60068-2-1	Appearance	No Damage
			Contact Resistance	≤ 70 mΩ
4-3-4	Humidity	Temperature: 40±2°C Relative Humidity: 90~95% Duration: 96 hours Test Method: MIL-STD-202F , Method 103	Appearance	No Damage
			Contact Resistance	≤ 70 mΩ
			Insulation Resistance	≥ 100MΩ
			Dielectric Strength	Must meet 4-1-3

ENTERY INDUSTRIAL CO., LTD.

INFRARED REFLOW CONDITION

- 1) Ascending time to preheating temperature 170°C shall be 40 seconds minimum.
- 2) Preheating shall be fixed at 160...180°C for 60...90 seconds.
- 3) Heating shall be fixed at 220°C for 50...60 seconds.
- 4) At 260±5°C peak shall be 10 seconds maximum.




Precaution in the connector handing.


1. Please try that the connector parallel is mated is mated
Into or unmated form the counterpart connector
in parallel.

2. Mating (into the counterpart connector)

At the time of mating please do not continue to mate the
connector if there is the gap.


A to the one side, please mate the connectors when the both
guides are guided.

 When mating plug with receptacle obliquely ,please make
mating within an angle of 5°.




3. Unmating (from the counterpart connector)

Please do not extract the one side of the printed circuit board.
Please extract the printed circuit board in parallel with the
connector.



4. Please do not bend the printed circuit board in the arrow
direction.



5. After mating connectors , fix the PCB/PWB in order not for them to disengage.

ENTERY INDUSTRIAL CO., LTD.

RELEASE HISTORY

Rev.	Revisions	Date	Executor	Description
A0	First Release	SEP-14-2009	JUNO	First Release
A1	RE201111014 RE201111028	NOV-18-2011	JIMMY	LCP 6130LX Change LCP E130I Cancel Packaging Spec